

Descrizione

I pannelli interni dal design moderno e lineare sono adatti per i tipi di ventilatori delle serie e², AB 30/60, RA 15-60, nonché per ALD, ALD-S e ALD-SV. I pannelli interni sono progettati per garantire un'installazione e una manutenzione semplici. Il filtro può essere rimosso e pulito facilmente.

Numero d'ordine	9/IBE	39 851
Numero d'ordine	9/IBK	40 087
Numero d'ordine	9/IBG	40 088
Numero d'ordine	9/IBK-H	40 179
Numero d'ordine	9/IBG-H	40 180

Installazione

L'installazione avviene inserendo (oppure, nel caso del modello 9/IBG, anche avviando) il telaio del filtro e il pannello nel condotto circolare 9/R 160. Il pannello interno deve scattare in posizione aperta. Sul retro è presente un'indicazione per le posizioni di apertura e chiusura.

Se necessario, tutti i pannelli interni e i telai di copertura possono essere puliti con un panno morbido e asciutto.

Le informazioni sul pannello interno fonoassorbente sono disponibili separatamente.

Dati tecnici

Materiale	Plastica ASA resistente ai raggi UV Vetro di sicurezza monolastra (ESG) per 9/IBG e 9/IBG-H
Colore	Bianco, simile a RAL 9016
Profondità richiesta nel condotto rotondo	20 mm
Dimensioni 9/IBE (L x A x P)	180 mm x 180 mm x 35 mm
Dimensioni 9/IBK (L x A x P)	180 mm x 191 mm x 60 mm
Dimensioni 9/IBG (L x A x P)	185 mm x 193 mm x 66 mm
Dimensioni 9/IBK-H (L x A x P)	191 mm x 180 mm x 77 mm
Dimensioni 9/IBG-H (L x A x P)	197 mm x 185 mm x 83 mm

Avviso

I prodotti e le loro immagini possono variare leggermente. A causa di continui sviluppi e/o di diversi fornitori di materiali, ad esempio per le materie prime, i colori possono variare leggermente (non per le parti a vista) o apparire diversamente nei cataloghi.



Pannello interno in plastica 9/IBE



Pannello interno in vetro 9/IBG



Pannello interno in plastica 9/IBK



*Coperchio interno igienico in vetro
9/IBG-H incluso filtro - F7*



*Coperchio interno igienico in
plastica 9/IBK-H incluso filtro - F7*

Description

The modern and puristic looking inner screens are suitable for the fan types of the e²-series, AB 30/60, RA 15-60 as well as the external wall diffusers. The inner screens are designed in such a way that installation and maintenance are kept as simple as possible. For example, the filter can be easily removed and cleaned.

Order No. 9/IBE	39 851
Order No. 9/IBK	40 087
Order No. 9/IBG	40 088
Order No. 9/IBK-H	40 179
Order No. 9/IBG-H	40 180

Installation

Installation is carried out by inserting (or screwing in the case of the 9/IBG) the filter frame and screen into the wall-tube 9 R 160.

The inner screen must snap into place in the open position. There is a corresponding note regarding the open and closed position on the back.

There is also a note on the correct positioning of the filter frame. If necessary, wipe the inner screen and the cover frame with a dry soft cloth.

Information on the internal sound insulation panel is available separately.

Technical data

Material	Synthetic material, UV resistant ASA Single-pane safety glass at 9/IBG and 9/IBG-H
Color	White, similar to RAL 9016
Min. depth required	20 mm
Dimensions 9/IBE (B x H x T)	180 mm x 180 mm x 35 mm
Dimensions 9/IBK (B x H x T)	180 mm x 191 mm x 60 mm
Dimensions 9/IBG (B x H x T)	185 mm x 193 mm x 66 mm
Dimensions 9/IBK-H (B x H x T)	191 mm x 180 mm x 77 mm
Dimensions 9/IBG-H (B x H x T)	197 mm x 185 mm x 83 mm

Note

Products and illustrations may vary slightly. Due to continuous product development and/or several suppliers e.g. for raw materials, colours, among other things, may vary slightly (not for visible parts) or be shown differently in brochures.



Standard Inner screen 9/IBE



Glas Inner screen 9/IBG



Comfort Inner screen 9/IBK



Hygiene Inner screen glass
9/IBG-H inklusive F7 filter



Hygiene Inner screen plastic
9/IBK-H inklusive F7 filter